

Samba Docker ipad

Création du docker-compose :

```
version: '3'
services:
  samba:
    container_name: samba-2to3
    hostname: samba
    image: sixeyed/samba
    volumes:
      - /mnt/2to:/media/2to:z
    ports:
      - "139:139"
      - "445:445"
      - "137:137/udp"
      - "138:138/udp"
    command: samba.sh -p -s "2to;/media/2to;yes;no;yes;all"
    mem_limit: 1g
    restart: always
```

Lancement du docker avec la commande :

```
docker-compose up -d
```

connection au docker

```
docker exec -it samba-2to3 bash
```

installation de packages complémentaires :

```
apt update
apt install -y samba-vfs-modules nano
```

nano /etc/samba/smb.conf

```
# Ipad OS
vfs objects = catia fruit streams_xattr
fruit:nfs_aces = no
ea support = yes
min protocol = SMB2
fruit:metadata = stream
fruit:model = MacSamba
fruit:veto_appledouble = no
fruit:posix_rename = yes
fruit:zero_file_id = yes
fruit:delete_empty_adfiles = yes
recycle:keeptree = yes
recycle:maxsize = 0
recycle:repository = .deleted
recycle:versions = yes
```

```
# Security
client ipc max protocol = SMB3
client ipc min protocol = SMB2_10
client max protocol = SMB3
client min protocol = SMB2_10
server max protocol = SMB3
server min protocol = SMB2_10
```

```
# Time Machine
fruit:delete_empty_adfiles = yes
fruit:time machine = yes
fruit:veto_appledouble = no
fruit:wipe_intentionally_left_blank_rfork = yes
```

Reboot du container ...